

CONOLOG®
ODSecure® System –
Getting attached is simple

CONOLOG ODSecure System


For reliable fixation of dentures on implants

The CONOLOG ODSecure abutment uses one of the industry's lowest profile connections to attach dentures and partial dentures to dental implants. With gingiva heights ranging from 1.0 to 6.0 mm, the CONOLOG ODSecure provides attachment solutions for even the challenging cases.

The abutment is designed for easy handling using a 1.25 mm screwdriver, hex, and is color-coded to ensure that the abutment matches the implant platform every time.

Low profile design

Total height of 2.0 mm with insert and housing cap



Screwdriver, hex

Delivered and torqued with a screwdriver, hex



Wear-resistant coating


Titanium nitride coating for enhanced durability and strength

Color-coded

Color coding to easily identify the proper platform size



The **housing cap** corrects up to 15° of divergence.



The **Xtend housing cap** corrects up to 25° of divergence.



Product detail

ODSecure abutments

New

	Article	Art. no.	Ø	GH
	CONELOG® ODSecure® Abutment Material Titanium alloy	C2273.3310	3.3 mm	1.0 mm
		C2273.3320		2.0 mm
		C2273.3330		3.0 mm
		C2273.3340		4.0 mm
		C2273.3350		5.0 mm
		C2273.3360		6.0 mm
		C2273.3810	3.8 mm	1.0 mm
		C2273.3820		2.0 mm
		C2273.3830		3.0 mm
		C2273.3840		4.0 mm
		C2273.3850		5.0 mm
		C2273.3860		6.0 mm
		C2273.4310	4.3 mm	1.0 mm
		C2273.4320		2.0 mm
		C2273.4330		3.0 mm
		C2273.4340		4.0 mm
		C2273.4350		5.0 mm
		C2273.4360		6.0 mm
		C2273.5010	5.0 mm	1.0 mm
		C2273.5020		2.0 mm
		C2273.5030		3.0 mm
		C2273.5040		4.0 mm
		C2273.5050		5.0 mm
		C2273.5060		6.0 mm

Accessories

	Article	Quantity	Color	Retention	Divergence	Art. no.
	ODSecure® attachment for Multi-unit abutment Ø 4.8 mm Material Titanium alloy	1	-	-	-	J2273.4801
	ODSecure® Xtend housing cap incl. Lab Processing Insert Material Titanium alloy / Nylon	2	yellow anodized	-	0°-50°	ODS-XH
	ODSecure® Housing cap incl. Lab Processing Insert Material Titanium alloy / Nylon	2	pink anodized	-	0°-30°	ODS-HCPM
	ODSecure® Retention cap insert Material Nylon	4	purple	HARD ca. 6 lbs / 2.7 kg	-	ODSRC-V
		4	clear	MEDIUM ca. 4 lbs / 1.8 kg	-	ODSRC-C
		4	pink	SOFT ca. 2.5 lbs / 1.2 kg	-	ODSRC-P
		4	yellow	EXTRA SOFT ca. 1.5 lbs / 0.6 kg	-	ODSRC-Y
	ODSecure® Lab processing insert Material Nylon	4	black	-	-	ODS-PM
	ODSecure® Impression coping Material Stainless steel / Nylon	2	-	-	-	ODSIC
	ODSecure® Castable male burnable Material Polystyrene	2	-	-	-	ODSCM

Product detail

Accessories

	Article	Quantity	Color	Art. no.
	ODSecure® Assortment kit Material Titanium alloy / Nylon / Silicone	2	-	ODS-CAK
	ODSecure® Block-out spacer Material Silicone	4	clear	ODS-BS
	ODSecure® Analog Material Titanium alloy	2	-	ODSA
	ODSecure® Cap extractor tool Material Stainless steel / Nylon	1	-	ODSCT

The **ODSecure Assortment Kit** contains a variety of different components such as a housing cap with four retention cap inserts, a lab processing insert and a block-out spacer.



BioHorizons Camlog Benelux B.V.

Pelmolenlaan 1 | 3447 GW Woerden | Nederland
info@camlog.nl | www.biohorizonscamlog.nl

Customer Service

Tel +31 (0)348 820 010 | info@camlog.nl

Headquarters

CAMLOG Biotechnologies GmbH | Margarethenstr. 38 | 4053 Basel | Switzerland
Phone +41 61 565 41 00 | Fax +41 61 565 41 01 | info@camlog.com | www.bhclgroup.com

All product names, whether or not appearing in large print or with the trademark symbol, are trademarks of BioHorizons Inc. or CAMLOG Biotechnologies GmbH, its affiliates, related companies or its licensors, unless otherwise noted.

Manufacturer of ODSecure® products:*

BioHorizons | 2300 Riverchase Center | Birmingham, AL 35244 | USA
ALTATEC GmbH | Maybachstr. 5 | 71299 Wimsheim | Germany

* This document refers to products from various approved manufacturers.
Please refer to the respective product label for manufacturer identification.

Valid from September 2025